

Exterior Vents Die Cast Aluminium

Mar 2023

Application: These Vents are designed for use on the external of Buildings to provide ventilation to internal rooms and to prevent a build up of Carbon monoxide or other dangerous gas. These can be used in bathrooms, kitchens, bedrooms and other habital rooms.



MODERN VERSION - To fit 4" (102mm) Pipe



MODERN VERSION - To fit 6" (150mm) Pipe



Round -
Facade 124mm Diameter
with 102mm Pipe Fitter on rear



Square -
Facade 118mm x 118mm
with 102mm Pipe Fitter on rear




Round -
Facade 170mm Diameter
with 150mm Pipe Fitter on rear




Square -
Facade 192mm x 192mm
with 150mm Pipe Fitter on

INSTALLATION DETAILS



A silicon adhesive is applied between the rear side of the vent and the pipe which holds the vent in position. Vents do not require to be rendered into the wall.

GULLY GRID - 6" x 6"



Gully Grid 6"x 6"-
Facade 150mm x 150mm

TRADITIONAL VERSION - 9"x 9" and 9"x 6"



Traditional 9"x 9"-
Facade 240mm x 240mm



Traditional 9"x 6"-
Facade 240mm x 164mm

ORDERING CODE

Size	Shape	Code	Details	Diameter to fit Pipe /Dimensions	Free Area(mm2)
4"	Round	ALU-VENTR40	Easy Fit Vent	102mm (4")	1,600mm ²
4"	Square	ALU-VENTS40	Easy Fit Vent	102mm (4")	1,600mm ²
6"	Round	ALU-VENTR60	Easy Fit Vent	150mm (6")	7,200mm ²
6"	Square	ALU-VENTS60	Easy Fit Vent	150mm (6")	6,680mm ²
9"x 6"	Rectangle	ALU-VENTT60	Traditional Vent	228mm x 150mm (9"x 6")	3,000mm ²
9"x 9"	Square	ALU-VENTT90	Traditional Vent	228mm x 228mm (9"x 9")	4,600mm ²
6"x 6"	Square	ALU-GRIDS60	Gully Grid	150mm x 150mm (6"x 6")	N/A

VeeLite Die-Castings, Six Cross Roads, Kilbarry, Waterford, Ireland

T:+353-51-875399

E: info@veelite.com

[VeeLite-die-castings.com](http://veelite-die-castings.com)

Specifications may change without prior notification. Technical Information on Request.